



GREEN CHEM
LABORATORIES

TECHNICAL DATA SHEET

NAME: FIBERGLASS EPOXY PATCH - CONCRETE

PART NUMBER(S): PO11-C



PRODUCT DESCRIPTION:

Fiberglass Epoxy Patch - Concrete is a fast-setting, epoxy putty that quickly repairs concrete and masonry. It also bonds to metals, wood, glass, and many plastics. After mixing, it forms a repair polymer that cures to a concrete-like color and texture. Suitable for interior or exterior use, it is resistant to water, chemicals, and temperature extremes and contains no solvents or VOCs. Concrete Epoxy is non-flammable, releases no noxious fumes and it won't shrink or pull away. Once cured, the application can be drilled, sawed, filed, tapped, sanded, and painted.

Features and Benefits:

- The ultimate solution for small or emergency repairs
- Easy-to-use and mistake-proof
- Bonds instantly with superior strength
- Saves hundreds of dollars in repairs
- Belongs in every toolbox

Use on:

Patch:

- Floors
- Curbs
- Steps
- Mortar
- Brick re-pointing
- Chipped concrete

Repair:

- Tile
- Statues
- Lawn ornaments
- Birdbaths
- Cemetery headstones
- Cracks and seams

Anchor:

- Bolts, screws
- Nails
- Railings
- Legs

Seal:

- Basement leaks
- Tie rod holes

SHELF LIFE AT 75°F (24°C) 24 months minimum.

TEMPERATURE LIMITS.

Continuous -40° to 250°F (-40° to 121°C).

Intermittent -40° to 300°F (-40° to 149°C).

CHEMICAL RESISTANCE.

Resistant to hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.

NOT INTENDED FOR STRUCTURAL APPLICATIONS.

Quantities:

24 UNITS/CASE



WWW.GREENCHEMLABS.COM

CUSTOMER SERVICE: 1-800-946-3151 | FAX: 1-800-336-9068

