



TECHNICAL DATA SHEET

NAME: FIBERGLASS EPOXY PATCH - PLASTIC

PART NUMBER(S): PO11-PL

PRODUCT DESCRIPTION:

Fiberglass Epoxy Patch - Plastic is a fast-setting epoxy putty that establishes a durable bond to most major plastic types without shrinking or pulling away. Once mixed, it forms a polymer compound that can be molded, wrapped around, or built up to repair just about anything made from rigid or semi-flexible plastic. After curing, it can be sawed, drilled, carved, sanded, or painted and is resistant to water, chemicals, and temperature extremes.

Certified by NSF International to NSF/ANSI Standard 61 for drinking water contact and conforms to ASTM D-4236.

Features and Benefits:

The ultimate solution for small or emergency repairs

- Easy-to-use and mistake-proof
- Bonds instantly with superior strength
- Saves hundreds of dollars in repairs
- Belongs in every toolbox
- Contains no solvents or VOCs.
- Non-flammable, releases no noxious fumes
- Won't shrink or pull away

Use on:

Rebuild:

- Rigid and semi-flexible plastics

Seal:

- Leaks in PVC and ABS plastic plumbing pipes

Repair:

- Automotive trim
- Appliance parts
- PVC furniture
- Vinyl siding
- Plastic downspouts and gutters

SHELF LIFE AT 75°F (24°C) 24 months minimum. TEMPERATURE LIMITS. Continuous -40° to 250°F (-40° to 121°C). Intermittent -40° to 300°F (-40° to 149°C). CHEMICAL RESISTANCE.

Resistant to hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.

NOT INTENDED FOR STRUCTURAL APPLICATIONS.

Quantities:

24 UNITS/CASE



WWW.GREENCHEMLABS.COM

CUSTOMER SERVICE: 1-800-946-3151 | FAX: 1-800-336-9068

