



TECHNICAL DATA SHEET



NAME: FOOD GRADE DRY SILICONE

PART NUMBER(S): QA491

PRODUCT DESCRIPTION:

Food Grade Dry Silicone is designed to lubricate equipment used in the packaging and processing industry. Slide Out leaves a non-staining, dry, pure silicone film to lubricate moving parts, reducing friction and wear. SLIDE OUT is heat stable from -35°F to 300°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. Complies with FDA regulations, CFR Title 21, paragraph 178.3570 when fully cured. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.

Features and Benefits:

- Concentrated formula. A little SLIDE OUT goes a long way
- Reduces friction between moving parts even for metal-to-metal contact surfaces. Parts last longer
- Clean, dry spray does not leave a sticky residue behind

Applications:

An excellent product for food processing plants, restaurants, apparel and accessory manufacturing, tank closure seals, plastic products, RV dealers, hotels/motels, machine shops, homes, service hinges, RV slide outs, auto/RV repair shops and institutions.

Specifications:

FORM: Solvent-Based Aerosol
COLOR: Clear
DETERGENCY: None
TOXICITY: 400 ppm OSHA TLV
WETTING ABILITY: Slight
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: <5°F TCC FLAME
EXTENSION: None SOLUBILITY IN WATER:
40% SPECIFIC GRAVITY: 0.76
% VOLATILE BY VOLUME: 96%pH: N/A
PROPELLANT: Hydrocarbon EVAPORATION
RATE: Fast BIODEGRADABILITY: None

Quantities:
12 UNITS/CASE



WWW.GREENCHEMLABS.COM

CUSTOMER SERVICE: 1-800-946-3151 | FAX: 1-800-336-9068

