



GREEN CHEM

LABORATORIES

HARD UP

PAINT SOLIDIFIER AND
ABSORBENT POWDER IN 1



SOLIDIFIES LATEX
AND ACRYLIC PAINT



ABSORBS
25 GALLONS



ABSORBS
SPILLS



DISPOSABLE

NET WT: 4 Gal

HARD UP can be used to solidify paint for quick and easy disposal OR used as a universal absorbent powder for spills. **HARD UP** works in minutes and one pail can solidify up to 25 gallons of paint. **HARD UP** can be used for latex, acrylic, and oil based paints.

DIRECTIONS FOR SOLIDIFYING PAINT

1. Shake or stir before use.
2. Use scoop provided to add to paint. A half-gallon of water- based paint requires approximately 20 ounces of **HARD UP**, using the included scoop. Other types of paints or stains may require more or less product.
3. Stir or shake. Latex paint will solidify in 3-4 minutes. Others may take longer.
4. Dispose in accordance with local regulations.

DIRECTIONS FOR ABSORBING SPILLS

1. Sprinkle over spill.
2. Give it a minute to absorb liquid.
3. Sweep up and dispose.

CAUTION

DISPOSAL NOTICE: Solidified paint must be disposed of in compliance with local, state and federal regulations. The manufacturer does not recommend disposal procedures.

WARNING: Persons sensitive to inert dust may experience coughing when exposed to heavy concentration of airborne material. If dust particles lodge in eyes, use standard eye wash solutions or water and allow eyes to clear. Do not use with hydrofluoric acid.

INGREDIENTS: Natural earth products and sodium polyacrylate

Green Chem Laboratories • www.GreenChemLabs.com • 1-800-964-3151