



GREEN CHEM

LABORATORIES

LIQUID RUBBER

WEATHERPROOFS, WATERPROOFS
& CHEMICAL RESISTANT



CHEMICAL
RESISTANT



WILL NOT CRACK,
PEEL OR METL



USE ON ROOFS
& FLASHINGS



WATERPROOFS
PIPES

19.4 oz. (550 g)



LIQUID RUBBER is a premium asphalt-based undercoating that creates an air and water-tight seal on surfaces. It weatherproofs, waterproofs, and is chemical resistant. This product will not crack, peel, melt, or drip from UV rays and is an excellent rust and corrosion inhibitor. **LIQUID RUBBER** can be used on: roofs, flashings, condensate drain pans, pipes, gutters, and more.

DIRECTIONS FOR USE

Shake can vigorously for one minute after mixing ball begins to rattle. Apply to clean dry surface not under 50°F. Spray with short even strokes from 14-18 inches.

COMPOSITIONAL INFORMATION

Contains Toluene (CAS#108-88-3), Solvent Naphtha (Petroleum), Light Aliphatic (CAS#64742-89-8), Isobutane (CAS#75-28-5), Calcium Carbonate (CAS#471-34-1), Propane (CAS#74-98-6), Carbon Black (CAS#1333-86-4), Crystalline Silica (CAS#14808-60-7). **DANGER:** Extremely flammable aerosol. Pressurized container: may burst if heated. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin irritation. May cause cancer. Suspected of damaging fertility or the unborn child.



PRECAUTIONARY STATEMENT

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations.

READ SAFETY DATA SHEET BEFORE USING

NOT FOR RETAIL SALE. INDUSTRIAL USE ONLY. NOTE to customers in California, UTAH, Lake Michigan Air Directors Consortium (LADCO) states, and Ozone Transport Commission (OTC) states: This product is sold to and is to be used exclusively by establishments which manufacture or construct goods or commodities. For use in the manufacturing process only.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Green Chem Laboratories • www.GreenChemLabs.com • 1-800-964-3151