Safety Data Sheet

SECTION 1: Product and company identification

Product name : ORANGE MUSTANG

Use of the substance/mixture : aerosol Product code : AA32

Company : GREEN CHEM LABORATORIES

1650 MARKET STREET

SUITE 3631

PHILADELPHIA, PA 19103 - US T 1-800-964-3151 - F 1-800-336-9068

Emergency number : INFOTRAC: 1-800-535-5053 OR 1-352-323-3500

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1 H222 Skin Irrit. 2 H315 Skin Sens. 1 H317 Asp. Tox. 1 H304

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US)







GHS02 GHS07 GHS08

Signal word (GHS US) : Danger

Hazard statements (GHS US) : Extremely flammable aerosol.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

heat, sparks, open flames, hot surfaces, Do not smoke Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing gas.

Wash thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves.

If swallowed: Immediately call a doctor, a POISON CENTER.

If on skin: Wash with plenty of water.

Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container to comply with local/regional/national/international regulations..

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures			
Name	Product identifier	%	GHS-US classification
Citrus Terpenes	(CAS-No.) 94266-47-4	60 – 80	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			Skin Sens. 1, H317
			Asp. Tox. 1, H304

Issue date: 9/17/2021 Revision date: 05/15/2015 Version: 1.0 Z_US GHS SDS 21 Page 1 of 7

Safety Data Sheet

HEAVY ALKYLAAT, SHELL	(CAS-No.) 64741-65-7	20 – 40	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			STOT SE 3, H336
			Asp. Tox. 1, H304
propane	(CAS-No.) 74-98-6	10 – 20	Flam. Gas 1, H220
			Press. Gas (Comp.), H280

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. show this sheet

where possible. Keep watching the victim. Keep victim warm and rested. Wash contaminated clothing before reuse.

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. Artificial respiration

and/or oxygen if necessary. IF INHALED: Do not apply mouth-to-mouth resuscitation. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediately consult a doctor/medical service. If experiencing respiratory symptoms:

Call a poison center or a doctor.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Get immediate medical advice/attention. Wash

contaminated clothing before reuse.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Immediately call a POISON CENTER/doctor. Rinse mouth. Do not induce vomiting without medical advice. Vomiting: prevent asphyxia/aspiration pneumonia. Ingestion of large quantities: immediately to

hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : None under normal use.

Symptoms/effects after skin contact : Dermatitis. Skin rash/inflammation. Irritation. Red skin. May cause an allergic skin reaction. Causes

skin irritation.

Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.

Symptoms/effects after ingestion : Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms may be delayed. Keep watching the victim.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Powder. Alcohol-resistant foam. Water fog. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. May liberate toxic gases. Combustion produces irritating gases.

Explosion hazard : Contains gas under pressure; may explode if heated.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : In case of fire and/or explosion do not breathe fumes. Move containers away from the fire area if this

can be done without risk. NEVER direct water jet on liquid. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a

flammable residue.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Consider initial downwind evacuation for at least 500 meters (1/3 mile). Evacuate unnecessary personnel. Stay upwind/keep distance from source. Gas is denser than air. May accumulate in low areas e.g. close to the ground. Vapours are heavier than air and may travel considerable distance to an

ignition source and flash back to source of vapours.

6.1.1. For non-emergency personnel

Issue date: 9/17/2021 Revision date: 05/15/2015 Version: 1.0 Z_US GHS SDS 21 Page 2 of 7

Safety Data Sheet

Protective equipment

: Do not enter without an appropriate protective equipment. Do not breathe gas/vapour. Do not touch spilled material. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with

no fire.

Emergency procedures : Ventilate the area thoroughly, especially low lying areas (basements, workpits etc). Advise local authorities if considered necessary.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid discharge to the environment. Do not contaminate water with the product or its container. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment

Eliminate every possible source of ignition. No open flames, no sparks, and no smoking. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Vapours are heavier than air and may spread along floors. Gas is denser than air. May accumulate in low areas e.g. close to the ground. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if safe to do so. Stop the leak. Turn leaking containers leak-side up to prevent the escape of liquid. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to disperse the vapours. Isolate area until gas has dispersed.

Methods for cleaning up

: Following product recovery, flush area with water. Clean thoroughly. Dispose as hazardous waste. Reference to other sections (13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Vapours may form explosive mixture with air. Exclude sources of heat, sparks and open flame. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use only explosion-free electrical equipment with earth. Do not re-use empty containers. Obtain special instructions before use. Reduce/avoid exposure and/or contact. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothing. Avoid prolonged and repeated contact with skin. Use only outdoors or in a well-ventilated area. Wear positive pressure air supplied respirator if required by safe entry procedures. Wear recommended personal protective equipment.

Hygiene measures

Wash thoroughly after handling. Use good personal hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Store locked up. Refrigerate.

Incompatible products

: Refer to Section 10 on Incompatible Materials.

Incompatible materials

: Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Storage area

: Store in a cool area. Aerosol 3.

Special rules on packaging

: meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HEAVY ALKYLAAT, SHELL (64741-65-7)

Not applicable

propane (74-98-6)			
ACGIH	ACGIH OEL TWA [ppm]	1000 ppm	
ACGIH	Remark (ACGIH)	Simple Asphyxiant	
OSHA	OSHA PEL TWA [1]	1800 mg/m³	
OSHA	OSHA PEL TWA [2]	1000 ppm	

Citrus Terpenes (94266-47-4)

Not applicable

8.2. Exposure controls

lssue date: 9/17/2021 Revision date: 05/15/2015 Version: 1.0 Z US GHS SDS 21 Page 3 of 7

Safety Data Sheet

Appropriate engineering controls Provide sufficient air exchange and/or exhaust. Ventilation rates should be matched to conditions. If

applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. . Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity

of any potential exposure. Avoid exposure, obtain special instructions before use.

Personal protective equipment Use appropriate personal protective equipment when risk assessment indicates this is necessary.

Gloves, Face shield, Protective clothing







Hand protection Avoid exposure, obtain special instructions before use.

Eye protection Avoid exposure, obtain special instructions before use. Face shield. Avoid contact with eyes.

Skin and body protection Avoid exposure, obtain special instructions before use. Avoid contact with skin. Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious

apron is recommended. It may provide little or no thermal protection. Respiratory protection

Avoid exposure, obtain special instructions before use. If permissible levels are exceeded use NIOSH

mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazard protection Use appropriate personal protective equipment when risk assessment indicates this is necessary. Consumer exposure controls

When using do not smoke. Avoid contact with eves. Avoid contact with skin. Keep away from food and drink. Use good personal hygiene practices. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid Appearance . Aerosol Odour Fruity

Odour threshold No data available No data available Melting point No data available Freezing point No data available 182.21 °F Estimated -156 °F Propellant estimated Boiling point Flash point

Relative evaporation rate (butylacetate=1) No data available Flammability (solid, gas) No data available Explosive limits No data available Explosive properties No data available Oxidising properties No data available

3.79 - 4.47 atm @ 70F estimated Vapour pressure

No data available Relative density Relative vapour density at 20 °C No data available Density 0.762 g/ml Estimated Solubility No data available Partition coefficient n-octanol/water (Log Pow) No data available Partition coefficient n-octanol/water (Log Kow) No data available Auto-ignition temperature 509.38 Estimated Decomposition temperature No data available Viscosity No data available

Viscosity, kinematic < 20 cSt No data available Viscosity, dynamic

SECTION 10: Stability and reactivity

Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Risk of explosion. Risk of ignition. Unstable. The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

Conditions to avoid

Heat. Open flame. Sparks. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point. . Incompatible materials.

Issue date: 9/17/2021 Revision date: 05/15/2015 Version: 1.0 Z US GHS SDS 21 Page 4 of 7

Safety Data Sheet

Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition may produce: Nitrogen oxides. Phosphorous oxide.

SECTION 11: Toxicological information

Information on toxicological effects 11.1.

Acute toxicity : Not classified

ORANGE MUSTANG		
LD50 dermal rat	2781 mg/kg	
LC50 Inhalation - Rat	712 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity Not classified Carcinogenicity : Not classified.

: Not classified Reproductive toxicity STOT-single exposure : Not classified. STOT-repeated exposure : Not classified

Aspiration hazard

Potential adverse human health effects and

symptoms

May be fatal if swallowed and enters airways.

Small amounts of liquid aspirated into the respiratory system during ingestion/vomiting may cause bronchopneumonia or pulmonary oedema. Dermatitis. Allergic skin rash. skin irritation. Redness,

Symptoms/effects after inhalation None under normal use.

Dermatitis. Skin rash/inflammation. Irritation. Red skin. May cause an allergic skin reaction. Symptoms/effects after skin contact

Causes skin irritation.

Direct contact with the eyes is likely to be irritating. Symptoms/effects after eye contact

Symptoms/effects after ingestion Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

SECTION 12: Ecological information

12.1. **Toxicity**

No additional information available

Persistence and degradability 12.2.

No additional information available

Bioaccumulative potential 12.3.

HEAVY ALKYLAAT, SHELL (64741-65-7)

Bioaccumulative potential No test data available.

SECTION 13: Disposal considerations

Waste treatment methods

Waste treatment methods

Additional information

Dispose of contents/container to comply with local/regional/national/international regulations. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. . Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. . Do not allow into drains or water courses. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this

product is considered a RCRA ignitable waste, D001. After recovery of solvent dispose of residue

as hazardous waste.

Containers, or internal liners coming from a container, having contained this product are also considered as hazardous wastes. This material and its container must be disposed of in a safe manner. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Handle uncleaned empty containers as full ones.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description (DOT) UN1950 Aerosols flammable, (each not exceeding 1 L capacity), 2.1

UN-No.(DOT) UN1950

Issue date: 9/17/2021 Revision date: 05/15/2015 Version: 1.0 Z US GHS SDS 21 Page 5 of 7

Safety Data Sheet

Class (DOT)

Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



Marine pollutant : Yes (IMDG only)



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

DOT Quantity Limitations Passenger : 75 kg

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft : 150 kg

only (49 CFR 175.75)

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : When transported by ground, this product may be eligible to be shipped as a Limited Quantity utilizing

the exception found at 49 CFR 173.306. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may be required.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
Proper Shipping Name (IMDG) : Aerosols

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No. (IATA) : UN1950
Proper Shipping Name (IATA) : Aerosols

Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylbenzene	100-41-4	0.01 – 0.1%
ethylbenzene	(100-41-4)	CERCLA RQ1000 lb



This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


SECTION 16: Other information

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures

before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Issue date: 9/17/2021 Revision date: 05/15/2015 Version: 1.0 Z_US GHS SDS 21 Page 6 of 7

Safety Data Sheet

Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Issue date: 9/17/2021 Revision date: 05/15/2015 Version: 1.0 Z_US GHS SDS 21 Page 7 of 7