# SAFETY DATA SHEET

1. Identification

**Product number** 1000009130 **PAINT STRIPPER Product identifier** 

11-12-2018 **Revision date** 

CPC **Company information** 

1000 INTEGRAM DRIVE

PACIFIC, MO 63069 United States

General Assistance 800-327-1835 Company phone

**Emergency telephone US** 1-866-836-8855 **Emergency telephone outside** 

1-952-852-4646

Version # 02

Supersedes date 04-17-2018 Recommended use Cleaner Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Health hazards Carcinogenicity Category 2

> Reproductive toxicity (the unborn child) Category 2 Specific target organ toxicity, single exposure Category 1 Specific target organ toxicity, repeated Category 2

exposure

**OSHA** defined hazards Not classified.

Label elements





Signal word

Extremely flammable aerosol. Suspected of causing cancer. Suspected of damaging the unborn **Hazard statement** 

child. Causes damage to organs. May cause damage to organs through prolonged or repeated

exposure.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

If exposed: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. Response Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

#### 3. Composition/information on ingredients

**Mixtures** 

Product name: TERAND 760 PAINT STRIPPER Product #: 1000009130 Version #: 02 Revision date: 11-12-2018 Issue date: 04-17-2018

Chemical name Common name and synonyms		CAS number	%	
Methylene Chloride		75-09-2	60 - 80	
Isobutane		75-28-5	2.5 - 10	
Methanol		67-56-1	2.5 - 10	
Propane		74-98-6	2.5 - 10	
Toluene		108-88-3	2.5 - 10	
Propylene Oxide		75-56-9	0.1 - 1	
Other components below reportable I	evels		1 - 2.5	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

During fire, gases hazardous to health may be formed.

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Dizziness. Nausea. Prolonged exposure may cause chronic effects.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Not available.

Most important

General information

symptoms/effects, acute and delaved

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire fighting

equipment/instructions

Specific methods

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol. General fire hazards

#### 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions** 

# 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Specifically Regulated Components	Туре	Value	
Methylene Chloride (CAS 75-09-2)	STEL	125 ppm	
,	TWA	25 ppm	
US. OSHA Table Z-1 Limits for Ai	r Contaminants (29 CFR 1910.100	0)	
Components	Туре	Value	
Methanol (CAS 67-56-1)	PEL	260 mg/m3	
		200 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
, ,		1000 ppm	
Propylene Oxide (CAS 75-56-9)	PEL	240 mg/m3	
		100 ppm	
US. OSHA Table Z-2 (29 CFR 1910	0.1000)		
Components	Туре	Value	
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Methanol (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm	
Propylene Oxide (CAS 75-56-9)	TWA	2 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
	mical Hazards Type	Value	
Components	Туре		
Components		1900 mg/m3	
Components Isobutane (CAS 75-28-5)	<b>Type</b> TWA	1900 mg/m3 800 ppm	
Components Isobutane (CAS 75-28-5)	Туре	1900 mg/m3 800 ppm 325 mg/m3	
Components Isobutane (CAS 75-28-5)	Type TWA STEL	1900 mg/m3 800 ppm 325 mg/m3 250 ppm	
Components Isobutane (CAS 75-28-5)	<b>Type</b> TWA	1900 mg/m3 800 ppm 325 mg/m3 250 ppm 260 mg/m3	
Components Isobutane (CAS 75-28-5) Methanol (CAS 67-56-1)	Type TWA STEL TWA	1900 mg/m3 800 ppm 325 mg/m3 250 ppm 260 mg/m3 200 ppm	
US. NIOSH: Pocket Guide to Cher Components  Isobutane (CAS 75-28-5)  Methanol (CAS 67-56-1)  Propane (CAS 74-98-6)	Type TWA STEL	1900 mg/m3 800 ppm 325 mg/m3 250 ppm 260 mg/m3	

Product name: TERAND 760 PAINT STRIPPER

# US. NIOSH: Pocket Guide to Chemical Hazards Value Components Type Value Toluene (CAS 108-88-3) STEL 560 mg/m3 150 ppm 150 ppm TWA 375 mg/m3

#### **Biological limit values**

ACGIH	<b>Biological</b>	<b>Exposure</b>	Indices
-------	-------------------	-----------------	---------

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
Methylene Chloride (CAS 75-09-2)	0.3 mg/l	Dichlorometha ne	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies** 

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Skin designation applies.
Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Methanol (CAS 67-56-1)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

100 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling -1

range

-16.28 °F (-26.82 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

10.5 % estimated

(%)

Flammability limit - upper

17.6 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 40 - 60 psig @20C estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available, estimated

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature 1007.48 °F (541.93 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Explosive properties** Not explosive. **Heat of combustion (NFPA** 9.79 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Specific gravity 0.159 estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability**Material is stable under normal conditions. **Possibility of hazardous**Hazardous polymerization does not occur.

reactions

**Conditions to avoid**Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation** May cause damage to organs by inhalation. May cause damage to organs through prolonged or

repeated exposure by inhalation.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the Dizz physical, chemical and toxicological characteristics

Dizziness. Nausea.

Information on toxicological effects

Acute toxicity

Product name: TERAND 760 PAINT STRIPPER

Components **Species Test Results** Isobutane (CAS 75-28-5) **Acute** Inhalation Gas LC50 1237 mg/l, 120 Minutes Mouse 52 %, 120 Minutes LC50 Rat 1355 mg/l Methanol (CAS 67-56-1) **Acute** Inhalation LC50 Cat 85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours Mouse 79.43 mg/l, 134 Minutes Rat > 115.9 mg/l, 4 Hours 82.1 mg/l, 6 Hours Oral LD50 Monkey 6000 mg/kg > 5000 mg/kg Pig Rat 1187 - 2769 mg/kg Methylene Chloride (CAS 75-09-2) **Acute Dermal** LD50 Rat > 2000 mg/kg, Days Inhalation Vapor LC50 49000 mg/m3, 7 Hours Mouse Oral LD50 Rat > 2000 mg/kg Propane (CAS 74-98-6) **Acute** Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l 658 mg/l/4h Propylene Oxide (CAS 75-56-9) **Acute** Dermal LD50 Rabbit 950 - 1250 mg/kg, 4 Hours 1.5 ml/kg, 4 Hours Inhalation LC50 4197 ppm, 4 Hours 4124 mg/m3, 4 Hours Oral LD50 Rat 382 - 587 mg/kg Toluene (CAS 108-88-3) **Acute Dermal** LD50 Rabbit > 5000 mg/kg, 24 Hours

Components	Species	Test Results
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
		25.7 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

#### Respiratory or skin sensitization

#### **ACGIH** sensitization

Propylene Oxide (CAS 75-56-9) Dermal sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Methylene Chloride (CAS 75-09-2) 2A Probably carcinogenic to humans. Propylene Oxide (CAS 75-56-9) 2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene Chloride (CAS 75-09-2)

Cancer

# US. National Toxicology Program (NTP) Report on Carcinogens

Methylene Chloride (CAS 75-09-2)

Propylene Oxide (CAS 75-56-9)

Reasonably Anticipated to be a Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

**Reproductive toxicity** Suspected of damaging the unborn child.

Specific target organ toxicity -

single exposure

Causes damage to organs.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not likely, due to the form of the product.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may

cause chronic effects.

#### 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Methanol (CAS 67-56-1	)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales prom	elas) > 100 mg/l, 96 hours
Methylene Chloride (CA	S 75-09-2)		
Aquatic			
Algae	IC50	Algae	500.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1689.5 mg/L, 48 Hours
		Water flea (Daphnia magna)	1250 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales prome	elas) 140.8 - 277.8 mg/l, 96 hours

Components		Species	Test Results
Propylene Oxide (CAS	S 75-56-9)		
Aquatic			
Crustacea	EC50	Daphnia	350 mg/L, 48 Hours
Toluene (CAS 108-88	-3)		
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

#### **Bioaccumulative potential**

#### Partition coefficient n-octanol / water (log Kow)

Isobutane	2.76
Methanol	-0.77
Methylene Chloride	1.25
Propane	2.36
Propylene Oxide	0.03
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

#### 14. Transport information

#### DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1
Subsidiary risk 6.1(PGIII)
Label(s) 2.1, 6.1
Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

#### **IATA**

UN number UN1950

UN proper shipping name Aerosols, flammable, containing substances in Division 6.1, Packing Group III

Transport hazard class(es)

Class 2.1

Subsidiary risk 6.1(PGIII)
Label(s) 2.1, 6.1
Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10P

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

**IMDG** 

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1
Subsidiary risk 6.1(PGIII)
Label(s) 2.1+6.1
Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

NOT a LTD QTY Not applicable.

DOT



#### IATA; IMDG



#### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methanol (CAS 67-56-1)

Methylene Chloride (CAS 75-09-2)

Propylene Oxide (CAS 75-56-9)

Listed.

Toluene (CAS 108-88-3)

Listed.

SARA 304 Emergency release notification

Propylene Oxide (CAS 75-56-9) 100 LBS OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene Chloride (CAS 75-09-2)

Cancer

Heart

Central nervous system

Liver Skin irritation Eye irritation

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name CAS number **Threshold** Threshold **Threshold** Reportable quantity planning quantity planning quantity, planning quantity, lower value upper value 10000 lbs Propylene Oxide 75-56-9 100

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methylene Chloride	75-09-2	60 - 80
Methanol	67-56-1	2.5 - 10
Toluene	108-88-3	2.5 - 10
Propylene Oxide	75-56-9	0.1 - 1

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)

Methylene Chloride (CAS 75-09-2) Propylene Oxide (CAS 75-56-9)

Toluene (CAS 108-88-3)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

Propvlene Oxide (CAS 75-56-9)

Safe Drinking Water Act Not regulated.

(SDWA)

# Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

Toluene (CAS 108-88-3) 594

#### **US** state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

Product name: TERAND 760 PAINT STRIPPER SDS US

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Isobutane (CAS 75-28-5) Methanol (CAS 67-56-1)

Methylene Chloride (CAS 75-09-2)

Propylene Oxide (CAS 75-56-9)

Toluene (CAS 108-88-3)

#### US. Massachusetts RTK - Substance List

Isobutane (CAS 75-28-5) Methanol (CAS 67-56-1)

Methylene Chloride (CAS 75-09-2)

Propane (CAS 74-98-6)

Propylene Oxide (CAS 75-56-9)

Toluene (CAS 108-88-3)

#### US. New Jersey Worker and Community Right-to-Know Act

Isobutane (CAS 75-28-5) Methanol (CAS 67-56-1)

Methylene Chloride (CAS 75-09-2)

Propane (CAS 74-98-6)

Propylene Oxide (CAS 75-56-9)

Toluene (CAS 108-88-3)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Isobutane (CAS 75-28-5) Methanol (CAS 67-56-1)

Methylene Chloride (CAS 75-09-2)

Propane (CAS 74-98-6)

Propylene Oxide (CAS 75-56-9)

Toluene (CAS 108-88-3)

#### **US. Rhode Island RTK**

Isobutane (CAS 75-28-5)

Methanol (CAS 67-56-1)

Methylene Chloride (CAS 75-09-2)

Propane (CAS 74-98-6)

Propylene Oxide (CAS 75-56-9)

Toluene (CAS 108-88-3)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methylene Chloride (CAS 75-09-2)

Propylene Oxide (CAS 75-56-9)

Listed: April 1, 1988

Listed: October 1, 1988

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Listed: March 16, 2012

Listed: January 1, 1991

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region Inventory name On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

۷۵٥

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 04-17-2018

 Revision date
 11-12-2018

Version # 02

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product name: TERAND 760 PAINT STRIPPER SDS US