



TECHNICAL DATA SHEET



NAME: SCALE BUSTER TOWER TREATMENT

PART NUMBER(S): AL69-4, AL69-5, AL69-30, AL69-55

PRODUCT DESCRIPTION:

This liquid scale and corrosion inhibitor is specifically formulated for open recirculating cooling tower systems in areas of high hardness and high alkalinity scaling waters. It also contains an additional polymer designed to help inhibit scale and deposition in a wide variety of aqueous systems.

Features and Benefits:

- Specifically designed as a treatment for open recirculating systems using high scaling, hard make-up water.
- Restores heat transfer efficiency for systems using hard water.
- Is completely compatible with other cooling tower maintenance products, such as biocides and biodispersants.

Effective against:

- Scale
- Mineral deposits
- Corrosion
- Lime
- Carbonate deposits
- Rust

Properties:

Appearance.....Yellow liquid
 Fragrance.....Mild odor
 Specific gravity.....0.11
 pH.....12.5-13.5

Directions Complete directions on product label
 Recommended for use with an automated continuous feed systems. Feed 25 - 50 ounces per 1,000 gallons of cooling water capacity. Maintain a residual molybdate level of between 1.2 and 2.4 ppm.

Quantities:

- 4X1 GALLONS (AL69-4)
- 5 GALLON PAIL (AL69-5)
- 30 GALLON DRUM (AL69-30)
- 55 GALLON DRUM (AL69-55)

