



**TECHNICAL DATA SHEET**



**NAME:** SUPER LUBE

**PART NUMBER(S):** AM333

**PRODUCT DESCRIPTION:**

**Super Lube Oil** with (PTFE) is a blend of premium synthetic PAO oil, Mineral oil, PTFE micron sized powder and powerful additives. This combination provides superior lubrication protection against friction, wear, rust and corrosion. Machinery lasts longer, downtime is reduced, and productivity is increased.

**Features and Benefits:**

- NSF H1 hydrolic oil
- Blend of premium synthetic PAO oil, mineral oil, PTFE micron sized powder
- Provides superior lubrication protection against friction, wear, and rust corrosion
- Machinery lasts longer, downtime is reduced, productivity is increased
- Temperature Rating: -45° F to 450° F
- Flash point 427° F

**Use on:**

- Plain/anti-friction and roller bearings, machine ways, machine tools, centralized lubricating systems
- Straight, helical, bevel and spiral gears
- Enclosed industrial gears
- Chains
- Gear head motors
- Conveyers
- Rubber
- Plastic
- Wood
- Leather
- Fabric
- Painted surfaces.
- USDA/NSF listed H-1 for incidental food contact surfaces

**Size:**  
7ml tube

**Color:**  
Clear

**Quantities:**  
20 UNITS/CASE



[WWW.GREENCHEMLABS.COM](http://WWW.GREENCHEMLABS.COM)

**CUSTOMER SERVICE: 1-800-946-3151 | FAX: 1-800-336-9068**

