







Offer empty container for recycling. If recycling is not available, discard container in trash.

KEEP OUT OF REACH OF CHILDREN - CAUSES SERIOUS EYE IRRITATION

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. For industrial and commercial use only. For additional information, see Safety Data Sheet.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

IF EYE IRRITATION PERSISTS: Get medical advice/attention.

NFPA® RATINGS: Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER: Water/7732-18-5; 2-butoxyethanol/111-76-2; Sodium Dodecylbenzenesulfonate/25155-30-0; Sodium Tripolyphosphate/7758-29-4; Sodium

Metasilicate/6834-92-0

Manufactured for: Green Chem Laboratories • www.GreenChemLabs.com • 1-800-964-3151



GREEN CHEM

LABORATORIES

SMOOTH OPERATOR

NON-ACID COIL CLEANER



NON-TOXIC











SAFE ON MOST SURFACES

Dilute this concentrate in warm or hot water for best performance. Spray, brush or mop onto surface and allow to penetrate and loosen deposits, then flush away with clean water.

For stubborn deposits, allow solution to remain on surface for 5 minutes, agitate with steel wool or sponge, then rinse with warm water.

Concrete, ceramic, tile, terrazzo, magnesite, vinyl, rubber, lockers, bulletin boards, and steel files and cabinets: Dilute 1 part cleaner in 30 parts water to clean.

Walls and lighting fixtures: Dilute 1 part cleaner in 20 parts water to clean

Plastic: Dilute 1 part cleaner in 15 parts water to clean.

Refrigerators, showers and pools, rubber clothing, skylights, air conditioners and heat **blower units, and electric fans:** Dilute 1 part cleaner in 10 parts water to clean.

Gymnasium equipment, tires, busses, trucks, heavy equipment, greasy floors, wooden mats, and ink on presses, walls, mats, and floors: Dilute 1 part cleaner in 6 parts water to clean Brick, grills, white wall, air filters, conveyors, engines, exhaust stains, machinery, metal stock, welding equipment, oven cleaning, deep fat fryers, flues, and canopy and ductwork: Dilute 1 part cleaner in 3 parts water to clean

NET CONTENTS: ONE GALLON (128 FL. OZ.)