



### — DANGER —

Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

### — FIRST AID —

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. **IF ON SKIN:** Wash off with soap and water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse. **IF SWALLOWED:** Rinse mouth. Get medical attention if symptoms occur.

### — WARNING —

This product can expose you to chemicals including Acetaldehyde, which is known to the state of California to cause cancer, and Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### — CONTAINS/CAS NUMBER —

Acetone (67-64-1), Dimethyl Ether (115-10-6), Isobutane (75-28-5), Ethylene Glycol (107-21-1), Isopropyl Alcohol (67-63-0), Propane (74-98-6), Tannic Acid (1401-55-4) and Oxalic Acid (144-62-7).

Green Chem Laboratories - [www.GreenChemLabs.com](http://www.GreenChemLabs.com) -  
1-800-964-3151



## GREEN CHEM LABORATORIES

**THUNDERCLAP** is a surface conditioner and primer designed to transform existing rust into a durable, protective coating that helps block moisture and slow future corrosion. It is formulated to react directly with rust for long-lasting performance rather than simply cleaning or covering the surface. Treated areas may be left as-is or top-coated with an oil-based paint to extend protection and improve finish.

### — DIRECTIONS —

For best results prepare surface by brushing the loose rust from the surface using a wire brush or sand paper. Clean the surface to remove grease and grime. Shake well before use. Hold can 8-12 inches from surface and spray a thin coat onto the surface. After the surface has dried, it will turn black. Then apply a second thin coat. Allow 48 hours to completely cure before painting while protecting it from rain or dew. For long lasting protection, seal with two coats of a high quality oil based paint. Do not apply if the surface temperature is below 50°F or above 90°F. Store in a cool dry place, protected from freezing or temperatures above 100°F.

### — CAUTIONS —

Extremely flammable. May cause burns to eyes, skin, and respiratory tract. Contents under pressure. Read carefully other cautions on back panel. Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Keep out of reach of children.

### — HMIS® RATINGS —

Health - 2, flammability - 3, physical hazard - 2, personal protection - X, 24-Hour Medical Emergency: 1-800-535-5053. Contains no ozone-depleting chemicals.

## THUNDERCLAP

AEROSOL RUST CONVERTER



NEUTRALIZES  
RUST



WORKS ON ALL  
METAL SURFACES



PROTECTS  
METAL



PAINTABLE

NET CONTENTS: 13 OZ. (368 G)