



GREEN CHEM LABORATORIES



WARNING

This product can expose you to Vinylidene chloride (1,1-Dichloroethylene), which is known to the State of California to cause cancer, and Ethylene glycol (ingested), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. For industrial and commercial use only. Keep out of reach of children.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER

Water/7732-18-5; Butoxyethanol/111-76-2; Tannic Acid/1401-55-4; Propylene Glycol/57-55-6; Oxalic Acid Dihydrate/6153-56-6; Vinylidene Chloride/75-35-4; Ethylene Glycol/107-21-1

Manufactured for: Green ChemLaboratories • www.GreenChemLabs.com • 1-800-964-3151

THUNDERCLAP

NEUTRALIZES RUST, CONVERTS IT TO A
PAINTABLE SURFACE, PREVENTS CORROSION



NON-TOXIC



NEUTRALIZES
RUST



WORKS ON ALL
METAL SURFACES



PROTECTS
METAL



PAINTABLE

NET CONTENTS: ONE GALLON (128 FL. OZ.)

THUNDERCLAP sprayable rust converter instantly bonds with rust, stops its growth, transforms it into a non-rusting, paintable surface, and prevents future rust formation. It is completely safe and easy to apply. **NOTE:** Ideal for use on machinery, equipment, structures, vehicles, railings, marine applications and more. Non-flammable, water based, low VOC, non-toxic, and emits no harmful fumes.

DIRECTIONS FOR USE

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: SHAKE OR STIR WELL BEFORE USING!

This product is ready-to-use. Do not dilute. Do not apply this product if the surface temperatures are below 50°F. Spray with an airless sprayer with 0.011-0.13 tip at 800-1200 psi. Adjust pressure as needed. One gallon will cover 200-300 square feet on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rust surfaces. Allow 48 hours cure time before application of the finished paint coat. For long-lasting protection of iron surfaces, the cured rust converter coating should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

IMPORTANT: Do NOT return unused material to original containers.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.